


公差表 / General tolerances (mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z	

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
SIZE: A4	mm / (inch)
NAME:	2ESARC-7.5-XXP-1Y-100A(H)
DRAWING NO.:	
SCALE:	
SHEET	REV
1 / 1	

2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准	UL Standard:	B	C
UL 标准	UL Standard:	B	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/15	/	300/10
VDE 标准 / VDE Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)	/	400/20	/
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	/	4	/
间距 / Pitch (mm) / 线数范围 / Poles	7.50 / N=02~12P		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		


宁波三安电子科技有限公司
 Sanan Electrical Technology Co., Ltd