


- 材质及电镀
- ① 主 体：PA66, UL94V-0
 - ② 盖 板：PA66, UL94V-0
 - ③ 夹 子：铜合金
 - ④ 按 钮：PA66, UL94V-0
 - ⑤ 弹 片：不锈钢

SECTION A-A



UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/10	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	300/10	320/13.	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/26~12		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~24P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:

SURFACE:


MAT NO.:

STATUS:

APPD.:

CHKD.:

DRFT.:


宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd

NAME: 15ESA0HDM-3.5

DRAWING NO.:

SIZE: A4

mm
inch

TYPE:

SCALE:

SHEET

公差/General tolerances(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10
±Z

D

C

B

A

D

B

A

1

2

3

4

5

6

2

3

4

5

6